Dino-Lite Europe - Phone: - Email:

# AM8917MZTL



**Brand:** Dino-Lite

**Product Code:** AM8917MZTL Edge Plus

### **Short Description**

High Optical Resolution 8.0 Megapixel Enhanced Flexible LED Control (eFLC) Automatic Magnification Reading (AMR) Long Working Distance Automatic Magnification Reading (AMR)

## **Description**

Capture stunning images with the AM8917MZTL 8-megapixel long working distance digital microscope. Engineered with a comprehensive set of features, including AMR, this model is designed to excel in both imaging and measurement-oriented tasks.



Metal housing



Enhanced Flexible LED control



Adjustable ~10x-140x



8,0 Megapixels 3840 x 2160





8 White LEDs switchable











#### The main features of the AM8917MZTL are:

- 8 Megapixels
- High Optical Resolution
- Automatic Magnification Reading (AMR)
- Extended Depth of Field (EDOF)
- Extended Dynamic Range (EDR)
- Depth Acquisition (DPQ)
- Enhanced Flexible LED Control (eFLC)
- Long Working Distance (LWD) Optics
- Adjustable Polarizer
- Robust Metal Housing
- $10x \sim 140x$  magnification (Edge shading occurs below 25x when previewing in 16:9 windows.)
- And more...

## **Optical Data Table**

WORKING	FIELD OF	FIELD OF	<b>DEPTH OF</b>
<b>DISTANCE</b> *	VIEW(X)	VIEW(Y)	<b>FIELD</b>
237.5	60.69	34.14	25.82
115.3	30.35	17.07	6.89
75.9	20.23	11.38	3.50
57.3	15.17	8.53	2.23
47.0	12.14	6.83	1.59
40.8	10.11	5.69	1.22
36.9	8.67	4.88	0.98
34.6	7.59	4.27	0.82
33.2	6.74	3.79	0.70
32.6	6.07	3.41	0.61
32.4	5.52	3.10	0.53
32.7	5.06	2.85	0.48
33.2	4.67	2.63	0.43
33.9	4.34	2.44	0.39
	DISTANCE * 237.5 115.3 75.9 57.3 47.0 40.8 36.9 34.6 33.2 32.6 32.4 32.7 33.2	DISTANCE * VIEW(X)   237.5 60.69   115.3 30.35   75.9 20.23   57.3 15.17   47.0 12.14   40.8 10.11   36.9 8.67   34.6 7.59   33.2 6.74   32.6 6.07   32.4 5.52   32.7 5.06   33.2 4.67	DISTANCE *   VIEW(X)   VIEW(Y)     237.5   60.69   34.14     115.3   30.35   17.07     75.9   20.23   11.38     57.3   15.17   8.53     47.0   12.14   6.83     40.8   10.11   5.69     36.9   8.67   4.88     34.6   7.59   4.27     33.2   6.74   3.79     32.6   6.07   3.41     32.4   5.52   3.10     32.7   5.06   2.85     33.2   4.67   2.63

Listed values may differ slightly \* Without front

Unit = mm

# Specification

Specification	
Lighting	
Light/ LED type	White
Number of LEDs	8
Optics	
Magnification	$10x \sim 140x$
Working distance	237.5 ~ 33.9 mm
Sensor	
Sensor type	CMOS
Resolution	8 Megapixel (3840 x 2160)
Maximum frame rate	10 fps at 8.0 MP, MJPEG 25 fps at 2.0 MP,
	MJPEG
Compatibility	
Interface	USB 2.0
Operating system	Windows 10/11
Supported image formats	BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP,
(Windows)	JP2, JPC, JPG, PGX, RAS, PNM
Supported video formats	WMV, FLV, SWF
(Windows)	
Housing	
Housing material	Metal housing
Dimensions	130 mm (H) x 33 mm (D)
Weight	120 g
Features	
Measurement	Yes
Calibration	Yes
Microtouch sensor	Yes
Information	
Package contents	N3C-C (Close Cap) N3C-D (Diffuser Cap) N3C-
	D2 (Opal Diffuser Cap) N3C-E (Extended Open
	Cap) N3C-L (Long Cap) N3C-O (Open Cap) N3C-
	S (Sidelight Cap)
Warranty information	2 years European warranty
Regulatory approval:	CE, FCC, ROHS
Price range	€1500,00 - €1700,00

# **Product Gallery**